



Modulární spínače RV 120

Modular switches RV 120

Technické údaje

Normy	EN 60947-3	
Počet pólů	1; 1 + N; 2; 3; 3 + N	
Jmenovitý proud	A	100 A
Jmenovitá frekvence	Hz	50 a 60
Kategorie použití	AC22	
Pracovní proud pro AC 23	A	40
Podmíněný zkratový proud	kA	3 (s pojistkami 100 AgG)
Elektrická trvanlivost	spínacích cyklů	4000
Mechanická trvanlivost	spínacích cyklů	8000
Průřez připojovacích vodičů	mm ²	50
Upevnění	na lištu DIN 35 × 7,5 EN 60715	
Krytí	IP 20; IP 40 po zabudování do rozvaděče za panel	
Teplota okolí	°C	-25 až + 55
Pracovní poloha	libovolná	

Technical data

Standards	EN 60947-3	
Number of poles	1; 1 + N; 2; 3; 3 + N	
Rated current	A	100 A
Rated frequency	Hz	50 a 60
Applications category	AC22	
Operating rated for	A	40
Rated conditional short-circuit current	kA	3 (with fuses 100 AgG)
Electrical endurance	switching cycles	4000
Mechanical endurance	switching cycles	8000
Wire crosssection	mm ²	50
Fixing	on DIN rail 35 × 7,5 EN 60715	
Degree of protection	IP 20, IP 40 after mounting in to board behind panel	
Ambient air temperature	°C	-25 to + 55
Working position	optional	

